


PART NUMBER EXPLANATION

EU Version



Connector Series

SSX 19pin Series

Number of Contacts

19

16

Contact Gender

M Male

F Female

Connector Type

V Inline

P Panel

Coupling Device

- Thread

D Threaded heavy duty locking ring

R Threaded rubber coated locking ring

Contact Plating

G Gold

S Silver

N No contact

Contact Type and Termination

C Crimp

S Solder

N No contact

K Armored crimp contact

Z Armored solder contact

Metric Backshell thread size and cable gland clamping ranges

MQ Thread size M 40 x 1.5 | Clamping range 15 - 23 mm

MP Thread size M 40 x 1.5 | Clamping range 19 - 28 mm

MR Thread size M 40 x 1.5 | Clamping range 22 - 32 mm

MS Spider: M 50 Grommet - 6 hole Ø 9 to 11,7 mm

ME Spider: M 50 Grommet - 8 hole Ø 10 mm

MF Spider: M 40 Grommet - 4 hole Ø 12 mm

MO Metric threaded backshell without cable gland

OO No backshell, no cable gland

Cable Clamp Type

N Plastic cable gland

R Metal basket weave grip strain relief (with wire mesh)

0 No further details

Additional contact features

T Pre-installed solder contacts

0 No further details

4 4mm² Crimp terminal wire section

6 6mm² Crimp terminal wire section

External Finish

0 Black painted

1 Black anodized

Colored anodized backshell available on request

Locking Ring Color


0 Black  (standard)

1 Green 

2 Red 

3 Yellow 

4 Blue 

5 Purple 

6 Orange 

Insulating Insert Color

N Black 

R Red 

Other insert colors available on request